

NCL Interior Primer



PRODUCT DESCRIPTION

NCL Interior Primer is made of inorganic fillers, additives, acrylic polymers etc. NCL cement primer is an acrylic based cement primer meant for application on concrete & cement plastered interior surfaces. NCL cement primer has good adhesion to the substrate and paint/plaster applied over it. The primer is alkaline in nature and hence best suited for application over concrete / cement plastered surfaces.

NCL cement primer also has excellent compatibility with NCL Alltek superfine and other NCL Alltek materials.



ADVANTAGES

- Ease of application with paint brush
- Long-lasting durability
- Good adhesion strength
- Eco-friendly
- Non-toxic
- Very low VOC
- Cost-effective



APPLICATION AREAS

Suitable for interior applications on cement plasters & concrete



PACK SIZES

20/10/4/1 litre pails



TECHNICAL DATA

Sl. No.	Attributes	Standard	NCL Buildtek Conforms
1	Color	Mfg. Spec	White
2	pH	Mfg. Spec	7.5 to 8.5
3	Weight / litre - g / cc	Mfg. Spec	1.39 - 1.4
4	Touch dry at 30°C	Mfg. Spec	4 hours
5	Number of coats	Mfg. Spec	1 if required 1 more coat can be done
6	Toxicity	Mfg. Spec	Non toxic



SURFACE PREPARATION

- Ensure that the wall's surface is free from dust, oil, grease, paints, loose foreign particles / materials and curing agents which may otherwise affect adhesion
- Fill the cavities on the wall



MIXING & APPLICATION

- Transfer the complete 1 litre primer material into a clean tub / bucket
- Add 1 litre water to 1 litre primer and mix thoroughly
- The above liquid should be free from lumps
- Apply the material on dry wall with a quality paint brush
- Allow a minimum of 8 hours before application of any coat
- Consume / apply the above mixed material within 12 hours



COVERAGE

The coverage is 120 sft / litre. The coverage may vary depending upon the condition of the substrate



SHELF LIFE

6 months



STORAGE

Store in moisture-free dry place



PRECAUTIONS

- Keep out of reach of children
- Keep in dry place
- Avoid inhalation of dust
- If it comes in contact with eyes or feeling of skin irritation, wash with plenty of plain water and consult a doctor

Marketed by:
NCL BUILDTEK LTD.
5th Floor, NCL Pearl,
Rail Nilayam Road, Secunderabad,
Telangana 522026
Tel: +91- 040-68313333
E-mail: contactus@nclbuildtek.com
Website: www.nclbuildtek.com